

8174 Rope Grab

Description

Lightweight, manual rope grabs move easily up and down vertical lifelines to provide continuous fall protection. In the event of a fall, Miller rope grabs lock quickly.

Materials

Rope Grabs:	Stainless Steel
Attachments	
Rope Lanyard:	5/8" (16mm) Synthetic Rope
Web Lanyard:	Polyester
Snap Hook:	Clear Zinc Chromate Plated Forged Alloy Steel Proof tested to 3,600lbs (16kN)

Technical

Min. Tensile Strength

Rope Grab:	3,600lbs (16kN)
Snap Hook:	5,000lbs (22.2kN)
SofStop:	5,000lbs (22.2kN)
Manyard:	5,000lbs (22.2kN)
Max Working Load:	310lbs (141kg)
Weights:	1.88lbs (0.85kg)
O-Ring Inner Diameter:	2.145" (54.4mm)

Certification

Meets OSHA 1910.66, 1926.502, ANSI A10.32, Z359.1 requirements.



Model #	Weight	Description
8174/U	1.88lb (.85kg)	Stainless steel, manual rope grab for use with 5/8" (16mm) or 3/4" (19mm) synthetic rope



PHONE: (1-246) 426-4935 • info@safetysupplyco.com • www.millerfallprotection.com

WARNING! THIS DOCUMENT PROVIDES AN OVERVIEW OF FALL PROTECTION PRODUCTS AVAILABLE FROM HONEYWELL AND CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE DATA. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. HONEYWELL RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THE PRODUCTS BE THOROUGHLY READ AND UNDERSTOOD PRIOR TO EACH USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.